

Wolfvision Eye-14 Live Camera System

Versatile image camera system

WOLFVISION

The powerful EYE-14 Live Image camera system gives outstanding results, whether used as a Ceiling Visualizer (without light), or when mounted on tripods, pan-tilt zoom mounts or wall mounts designed for video or surveillance camera with an impressive range of powerful features to capture your presentations and lectures for your students.

Key Features

Centre Lasermarker

A small laser light dot projected into the centre of the camera's pickup area making it easy to position objects in the centre of the camera's field of vision for optimal image capture. The laser point is also synced with the camera so it doesn't appear in any onscreen or recorded images.

Plug-and-Play Connectivity

The system supports the UVC standard, providing plug-and-play connectivity to Windows, Linux and Mac OS devices. The memory is also flexible for storing your content, with internal memory and external memory able to be used with the unit.

Large Zoom Range

With x14 optical zoom, the Eye-14 gives great flexibility in presentations, with large zooms and small postage stamps can easily be picked up, with a x4 digital zoom providing further flexibility for your captured content.

Powerful Full HD cameras

Features a 1-CMOS native 1080p HD camera giving 980 lines of visible resolution in every part of the picture

Optional Dry-Ease Working Surfaces

Provides a working surfaces enable you to use the camera system as a whiteboard/digital flip chart for making written notes during lectures or presentations.

Power over Ethernet

The LAN port includes Power over Ethernet Plus functionality, allowing you to save on cabling and installation costs.

HD Video Recording

On board recording functionality enables entire presentations and lectures to be captured in exceptional quality. Distribution of content is also easy through the software components, including the ability to stream to devices, both internally over the network and over the internet.



Product Specification

Features

Camera	1-CMOS 1/3"
Frames per second	30fps in all resolutions
Effective Pixels	1920 x 1080
Converted Output signals (4:3 & 5:4)	SXGA (1280 x 1024) / XGA (1024 x 768) / SVGA (800 x 600) / UXGA (1600 x 1200)
Converted Widescreen output signals (16:9 & 16:10)	WUXGA (1920 x 1200) / WXGA (1280 x 800) / 720p HD (1280 x 720)
Resolution (measured)	980 lines
Brightness Control with White Balance Adjustment	Automatic and Manual
Focusing Modes	High Speed Continuous Auto-focus / Manual Focus
Centre Lasermarker	Yes, single dot, in centre of working surface, invisible on screen
Live to freeze comparison	Yes, Picture-in-Picture and side by side
On-screen menu/help	Yes
Free firmware updates	via USB, LAN, USB stick
vSolution Link Pro software	Yes, included for Remote Management and firmware updates
Lens type	f = 4.7 - 66 mm
Total Zoom	x 56
Optical Zoom	x 14
Digital Zoom	x 4

Wolfvision Eye-14


UVC	Yes
User-defined settings on USB stick	Yes
User programmable presets	3
Image memory	8 GB internal memory + additional storage on USB stick or external hard drive
Browsable memory	Yes, scrollable thumbnails + 1 larger preview image
Image Memory	1 image freeze
Alternative image display	Negative image / negative-blue image / black and white image
Seamless cross-fading between image sources	Yes
vSolution App compatible	Yes, wireless control via mobile app
LAN Streaming Modes	Multicast and Unicast RTP H264 + audio / RTP MJPG + audio / MJPG
Onboard video recording including audio	Yes - 720p HD, up to 30 frames per second, AVI container, H.264 codec, .AVI file format
Advanced controlling with professional protocol	Yes, via LAN and USB
Anti-theft devices	T-Lock (Kensington® Lock)
Tripod mount/Ceiling Mount	2 tripod mounts (top and bottom, 1/4-20 UNC) plus u-shaped mounting clip

Product Specification

Wolfvision Eye-14

Connectivity

HDMI out	x1
RGB out	x1
IP addressable LAN port	x1 - 10/100Mbps with PoE+
USB 2.0 device port	x1
USB 2.0 host port	x1
Audio In	x1
Line Out	x1
Advanced controlling with professional protocol via LAN	Yes, wireless control via mobile device
Dimensions in operation	L127mm x W125mm x H91mm
Weight	1kg
Infrared remote control	Yes. Optional external receiver (with 10m cable and status LED)
Plenum rated	Yes
Power	External power pack, multi range 100 - 240 V, Power over ethernet plus (IEEE 802.3at standard, adjustable standby power consumption
Power Consumption	21W
Warranty	5 years



Zoom



VGA




Central Laser Marking



5 Year

Warranty



HDMI



All resolutions at 30FPS