Wolfvision vSolution Cam

Simplicity is the ultimate sophistication



The vSolution Cam demonstrates that simplicity truly is the ultimate sophistication. Drawing on more than 40 years' experience and expertise, we have engineered a new entry level Visualizer system, streamlined to include only its essential core components.

Key Features

Excellent Picture Quality

A 1-CMOS ultra-high resolution camera with 1080p HD output / 30 frames per second, and sRGB colour precision, provides measured image resolution (Ø) of 980 lines in every part of the picture.

Designed for ease of use

For maximum usability, focus, brightness, white balance etc., are all adjusted automatically, you only need to use the zoom buttons. Continuous autofocus recognises all objects quickly and precisely, and when required, manual focusing is also available.

Easy External Control

Can be controlled directly via Cynap. or from other external devices such as a room control system, a video conferencing system or a computer via USB and LAN.

Flexible imaging

Features a default x 4 HD zoom, which maintains optimal picture quality. A 10 x extended digital zoom can also be selected on the on-screen menu.

Capture your handwriting

Self-adhesive dry-erase working surfaces are available as optional accessories, enabling you to write onto, and erase directly from the pick-up area, using suitable whiteboard pens and erasers.

Energy efficiency

The LAN port provides Power over Ethernet (PoE) compatibility with devices meeting the IEEE 802.3af- 2003 standard. saving cables and installation costs.

Adjustment-free lighting

The maintenance-free LED light system is optimized for the entire pick-up area, which means there is never any need for manual adjustment of the light.





Technology Summary

Wolfvision vSolution Cam

















1080p at 30FPS







Product Specification

WO	itvision	VSOILIT	ion Cam

Features

1-CMOS 1/3", 30 frames per second Camera

Total Pixels 13.2 Megapixels

Resolution 4224 x 3136

Converted widescreen

output signals (16:9)

Colour Reproduction /

precision sRGB colour precision

Measured image

resolution 980 lines

Brightness Control Automatic / Manual (in on-screen menu)

1080p (1920 x 1080) / 720p (1280 x 720)

via USB, LAN, vSolution Link Pro software

White Balance

Automatic / Manual **Adjustment**

Autofocus / Speed Yes (continuously high speed)

Manual Focus Yes

On-screen menu & help

Firmware Updates

Zoom x 4 HD Zoom (x 10 extended digital zoom)

Yes

Wide angle f = 3.81mm Lens type

Max Object height 240 mm / 290 mm with Riser

Max Size of pick up Length: 268mm/195mm, Width: 362 mm/

area (using zoom 4:3) Length: 311mm/226mm, Width: 419mm with

Riser Plate

Min size of pick up area 44 mm x 22.5 mm / 45.5 mm x 25 mm with

Riser Plate

Depth of focus on small

object (66 x 36 mm) 60 mm Depth of focus on large

object (350 x 196 mm) 100 mm

Riser Plate to increase

camera height Optional

Light Source LED (30,000 hours)

UVC Compatible Yes (Windows, macOS & Linux)

Yes

1 image freeze

vSolution Cynap

Compatible

Reflection-free pick-up

area Yes, entire pick-up area **Image Memory**

Connections

HDMI

Power

LAN x 1 (IP addressable)

mini USB

USB x1 (for control and firmware updates)

x 1

x 1

Advanced controlling Yes, and LAN and USB

Anti-theft devices Kensington T-Lock & table lock bolt

Operation Dimensions L264 mm x W165 mm x H399 mm

12V: multi range 100 - 240V, 24W

Power over Ethernet Compatible

Warranty 5 years

Included Accessories Power supply (1.5m cord), User Manual

Optional Accessories Riser Plate, Dry-erase Working surface, RS232

adapter, HDBaseT transmitter, Lightboxes

